

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

glimtrex Hardwax-Oil gloss 101003

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Surface treatment of wood and other materials

1.3. Details of the supplier of the safety data sheet

Manufacturer

glimtrex GmbH

Orkotten 68

48291 Telgte

Telephone no.

+49 (0) 2504 88887-111

Fax no.

+49 (0) 2504 88887-112

E-mail address

info@glimtrex.de

1.4. Emergency telephone number

Germany: +49 (0) 30 30686700

2. Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Supplemental information

EUH066

Repeated exposure may cause skin dryness or cracking.

EUH210

Safety data sheet available on request.

Further supplemental information

Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

2.3. Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB) (if not listed in Section 3).

3. Composition/information on ingredients ***

Hazardous ingredients ***

Naphtha (petroleum), hydrotreated heavy

CAS No. 64742-48-9

EINECS no. 265-150-3

Registration no. 01-2119457273-39

Concentration >= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

Asp. Tox. 1 H304

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

EINECS no. 918-167-1
 Registration no. 01-2119472146-39
 Concentration ≥ 10 < 25 %
 Classification (Regulation (EC) No. 1272/2008)
 Flam. Liq. 3 H226
 Asp. Tox. 1 H304
 Aquatic Chronic 4 H413

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics

CAS No. 246538-78-3
 EINECS no. 920-901-0
 Registration no. 01-2119456810-40
 Concentration ≥ 1 < 10 %
 Classification (Regulation (EC) No. 1272/2008)
 Asp. Tox. 1 H304
 EUH066

Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics

EINECS no. 927-285-2
 Registration no. 01-2119480162-45
 Concentration ≥ 1 < 10 %
 Classification (Regulation (EC) No. 1272/2008)
 Asp. Tox. 1 H304

Polyamine amide salt

Concentration ≥ 1 < 10 %
 Classification (Regulation (EC) No. 1272/2008)
 Skin Irrit. 2 H315

Note

For explanation of abbreviations see section 16.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) (if not listed in Section 3).

4. First aid measures**4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

After ingestion

Do not induce vomiting. Take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically.

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist

Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

Other information

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance. Do not process in the same cabin together with highly flammable material (e.g. CN lacquer) => fire hazard through self ignition! Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Storage classes

Storage class according to TRGS 510 10 Flammable liquids

Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

7.3. Specific end use(s)

See exposure scenario, if available.

8. Exposure controls/personal protection

8.1. Control parameters

Exposure limit values

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

List	TRGS 900
Value	600 mg/m ³

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

Maximum limit value: 2(II); Status: 05/2013

Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics

List	TRGS 900
Value	300 mg/m ³
Status:	08/2019

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics

List	TRGS 900
Value	600 mg/m ³
Maximum limit value:	2(II); Status: 01/2012

Naphtha (petroleum), hydrotreated heavy

Value	300 mg/m ³
Status:	08/2019

Other information

-

8.2. Exposure controls**Exposure controls**

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Respiratory protection not applicable; Use breathing apparatus if exposed to vapours/dust/aerosol.
Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material	Nitrile rubber
Material thickness	>= 0,4 mm
Breakthrough time	>= 30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Eye protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

Form	liquid
Colour	colourless
Odour	characteristic
Odour threshold	
Remarks	not determined
pH value	
Remarks	not determined
Melting point	
Remarks	not determined
Freezing point	
Remarks	not determined
Initial boiling point and boiling range	
Value	100 to 214 °C
Flash point	
Value	> 60 °C
Evaporation rate	
Remarks	not determined
Flammability (solid, gas)	
not determined	
Upper/lower flammability or explosive limits	
Remarks	not determined
Vapour pressure	
Remarks	not determined
Vapour density	
Remarks	not determined
Density	
Value	appr. 0,873 kg/l
Temperature	20 °C
Solubility in water	
Remarks	not determined
Solubility(ies)	
Remarks	not determined
Partition coefficient: n-octanol/water	
Remarks	not determined
Ignition temperature	
Remarks	not determined
Decomposition temperature	
Remarks	not determined
Viscosity	
Remarks	not determined
Efflux time	
Value	42 to 55 s
Temperature	20 °C

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

Method	DIN 53211 4 mm
--------	----------------

Explosive properties

evaluation	not determined
------------	----------------

Oxidising properties

Remarks	not determined
---------	----------------

9.2. Other information**Non-volatile content**

Value	43,5	%
Method	calculated value	

Other information

This information is not available.

10. Stability and reactivity**10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6. Hazardous decomposition productsCarbon monoxide and carbon dioxide, nitrous oxides (NO_x), dense black smoke, No decomposition if used as prescribed.**11. Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Acute dermal toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Acute inhalational toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

Skin corrosion/irritation (Components)**Polyamine amide salt**

Species	rabbit
evaluation	Irritating to skin.

Serious eye damage/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Sensitization

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Mutagenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Reproductive toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Carcinogenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)**Single exposure**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Repeated exposure

Remarks	Based on available data, the classification criteria are not met.
---------	---

Aspiration hazard

Based on available data, the classification criteria are not met.

Other information

No toxicological data are available.

12. Ecological information**12.1. Toxicity****General information**

For this subsection there is no ecotoxicological data available on the product as such.

Fish toxicity (Components)**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics**

Species	Fish	
LC50/EC50/IC50/LL50/EL50	>	100 mg/l
0		
Duration of exposure	=	96 h

Daphnia toxicity (Components)**Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics**

Species	Daphnia magna (Water flea)	
EC50	>	1000 mg/l

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

Duration of exposure 48 h

12.2. Persistence and degradability

General information

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability (Components)

Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics

evaluation Not readily biodegradable.

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics

evaluation Not readily biodegradable.

12.3. Bioaccumulative potential

General information

For this subsection there is no ecotoxicological data available on the product as such.

Partition coefficient: n-octanol/water

Remarks not determined

12.4. Mobility in soil

General information

For this subsection there is no ecotoxicological data available on the product as such.

Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

General information

For this subsection there is no ecotoxicological data available on the product as such.

12.6. Other adverse effects

General information

For this subsection there is no ecotoxicological data available on the product as such.

General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.

13. Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances

EWC waste code 200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

modified product

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

EWC waste code

080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

Dried residues

EWC waste code

080112 - waste lacquers and waste paint except those falling under 080111

Disposal recommendations for packaging

EWC waste code

150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

Germany: KBS system for sheet covering

Completely emptied packagings can be given for recycling.

14. Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Water Hazard Class (Germany)**

Water Hazard Class

WGK 2

(Germany)

Remarks

Derivation of WGK according to Annex 1 No. 5.2 AwSV

VOC

VOC (EU)

56,4

%

492

g/l

Other information

All components are contained in the TSCA inventory or exempted.

15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

16. Other information**Hazard statements listed in Chapter 3**

EUH066

Repeated exposure may cause skin dryness or cracking.

H226

Flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

H413

May cause long lasting harmful effects to aquatic life.

CLP categories listed in Chapter 3

Aquatic Chronic 4

Hazardous to the aquatic environment, chronic, Category 4

Asp. Tox. 1

Aspiration hazard, Category 1

Flam. Liq. 3

Flammable liquid, Category 3

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 4 / DE

Revision: 07.05.2020

Replaces Version: 3 / DE

Print date: 06.07.20

Skin Irrit. 2

Skin irritation, Category 2

Abbreviations

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG - International Maritime Code for Dangerous Goods

IATA - International Air Transport Association

IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS - Globally Harmonized System of Classification and Labelling of Chemicals

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS - Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL - Lowest Observed Adverse Effect Level

LOEL - Lowest Observed Effect Level

NOAEL - No Observed Adverse Effect Level

NOEC - No Observed Effect Concentration

NOEL - No Observed Effect Level

OECD - Organisation for Economic Cooperation and Development

VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (***). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.